DETAILS OF EQUIPMENT, ACCESSORIES AND TOOLING ON MACHINE

3 1/2 RB-6 SERIAL # 94835

40 HP, 1200RPM, 550 Volts 3 PH 60 CYCLE TEFC BALL EARING MOTOR

Standard universal chip conveyor

Trabon centralized lubrication system, Grease

Compliance sound level 80 DBA

Collet pad type 'CB'

Feeder pad type 'PN'

1st Adj. boring bar holder, F24973 1-1/4 Dovetail Form Tool holder.

Adj. knee tool

2nd Adj. boring bar holder

3rd Position 10 deg. Flat type recess fixture

 $4\mbox{th}$ position Internal thread chasing attachment and drive nut with 3 matched

thread chasing tools

5th Position wedge type cut-off tool and holder

5th Position air operated stencil assembly TG-993609

6th Position 1 1/4 dovetail form tool holder

1st- 2nd Position double decker 1- 1/4 dovetail

Finish form and skive holder

Power Reverse

ADDITIONAL TOOLS AND HOLDERS AVAILABLE UPON REQUEST

GEARS FOR 3-1/2 RB-6

| | Available | Available | | | |
|----|-----------|-----------|---|--|--|
| 28 | | | | | |
| 30 | | 74 | | | |
| 32 | | 72 | | | |
| 34 | | 70 | | | |
| 36 | 1 | 68 | 1 | | |
| 38 | | 66 | | | |
| 40 | | 64 | | | |
| 42 | | 62 | | | |
| 44 | | 60 | | | |
| 46 | | 58 | | | |
| 48 | 1 | 56 | 1 | | |
| 50 | | 54 | | | |
| | | 52 | | | |

3 1/2 RB-6 COLLET AND FEEDERS INVENTORY

| SIZE | SHAPE | SOLID | COLLET | RINGS | SOLID | PUSHER |
|------|-------|---------|--------|-------|--------|--------|
| | | COLLETS | PADS | | PUSHER | PADS |

6 MASTER COLLETS6 PUSHER TUBES6 MASTER PUSHER

TYPE COLLET PADS -- CB
TYPE FEEDER PADS -- PN

CAMS

18.5" DIAMETER (Main Tool Slide) 11" DIAMETER FEED OUT 8" DIAMETER

T. S. Lead cam 1" A82290
T. S. Guard cam 1" A82304

A823250-T

A82327-T

A82320

Lead cam Guard cam A827790 - 2" FEED A827800 - 2" RETURN 4th Position top rear

4 PIECE BOX THREAD CAM SET .045

TA942888 LEAD TA942889 GUARD TA942890 RETURN

TA942891 RETURN GUARD

3rd Position top front

Lead 1/2" - AW725005-00 Lead Guard 1/2" - AW735005-00

Return - A96793 Return Guard - A96794

CAMS continued

8" Return

SPACER

8" RETURN GUARD

10 DIAMETER (Cross Slide (1st AND 6th) Lower front and rear slide 5 1/4" DIA. Drum (2nd Position Side slide)

5 1/4" DIA. Drum (5th Position Side slide)

3/8 - LEAD - BR600003-75

3/8" - LEAD GUARD BR 605003-75

5/16 - Lead - BR 600003-12

5/16 - Lead Guard - BR 605003-12

RETURN - A96821

2 RETURN GUARD - A96815

USING DOUBLE DECKER NO CAM 7/16- Lead - A955700 7/16- Lead GUARD - A955720

RETURN - A955710

RETURN GUARD - A955730

ADDITIONAL SIZES AVAILABLE UPON REQUEST